60A AC AND LEAKAGE CURRENT CLAMP METER



CAT II 600V

Part No. C2006

The C2006 is a low current measuring clamp meter including a low 20mA range. It is suitable for detecting leakage current in earth conductors, making it handy for testing appliances. This clamp has two ranges 0 – 20mA and a high range to 60 A. Compact and small with a 31mm diameter jaw opening. Used with appliance adaptor C-DEL to test for leakage current in appliance testing (run test) according to AS3760.

- 3 digit, 1999 count LCD
- CATIII 600V
- Auto/manual ranging
- Data hold
- Low battery display
- Jaw opening ø31mm

EA QTY 1

Compliance and Safety	IEC61010-1 CAT II 600V
Contents	The C2006 comes in a gift box with test leads and operating manual.
Dimensions	L208 × W38 × T529mm
Batteries	2 x 1.5V AAA
Weight	110g
Replacement Test Leads	AL28-1

Feature	Range	Accuracy
AC Current	2/20mA 60A (<50A) (>50A)	±2% ± 5 ±2% ± 5 ±3% ± 5

AC LEAKAGE CURRENT CLAMP



CAT III 600V

Part No. C2010

The C2010 is a very accurate current clamp capable of measuring in the low mA range. It is suitable for detecting leakage current in earth conductors. Feature packed with functions such as max recording, relative measurement, backlight, etc.

- 3½ digit, 3999 Count LCD
- CATIII 600V
- Auto/manual ranging
- Max recording
- Backlight LCD
- Continuity with buzzer
- Diode check
- Data hold
- Duty cycle 0.1% to 99.9%
- Low pass filter for voltage measurement
- Temperature type-K thermocouple
- 10 MΩ input – voltage range
- Resistance range - 250V AC/DC PTC circuit protection

EA QTY 1

Compliance and Safety	IEC61010-1 CATIII 600V
Contents	Each C2010 is supplied in a gift box with operating manual, soft carry bag, batteries, thermocouple, test leads.
Dimensions	L260 x W92 x T55mm
Batteries	3 x AAA
Weight	+ 400g
Spare Leads	AL28-1

Feature	Range		Accuracy
AC Current	20m/200m/2/20/200/600A	50 to 60Hz	±1% +8
		30Hz to 10kHz	±3% +10
AC Voltage	200m/2/20/200/600	50 to 60Hz	±0.7% +3
DC Voltage	200m/2/20/200/600V		±0.8% +5
Resistance	200Ω/2k/20k/200k/2M		±1% +2
	20MΩ		±2% +5
Temperature	-20°C to 0°C		±2% +5
	1° to 400°C		±1% +3
	401° to 1000°C		±2% +3
Jaw Size	31x40mm		

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.